



THE BELT RAILWAY COMPANY OF CHICAGO

YARDMASTER NOTICE

#2019-Y004

Effective 0001, May 17, 2019

To: ALL CONCERNED

Subject: Distributed Power (DP) Outbound Train Restrictions (CSXT)

When making up trains, designated by the Terminal Manager, to be operated in a Distributed Power (DP) configuration, observe the following restrictions.:

Note that these restrictions apply in addition to any other train make-up restrictions that are in place for the train. For the purposes of hazardous materials compliance, a DP Remote Consist is considered the same as any other locomotive.

In the event of a conflicting train make-up requirement, contact the Terminal Manager for instructions.

By definition, a DP Remote Consist is a locomotive consist located at other than the head end of the train.

DP Locomotive Placement:

When placing mid-train DP Remote Consists in a train the DP Remote Consist must be placed as follows:

- Not less than 1250 feet behind the lead locomotive consist
- Not closer than mid-train between the head end locomotive consist and the rear of the train.

Exception: To maintain block integrity, DP Remote Consists can be placed up to 1000 feet ahead of the designated mid-train point when necessary.

Maximum Train Lengths (DP Trains with Rear End DP Locomotive Consists):

- Manifest trains operating with a single DP consist on the Rear of the train must not exceed 9000 feet between the lead locomotive consist and the remote DP locomotive consist.

Note: If unable to comply with these requirements, the DP Remote Consist must be placed in idle and not used for power.

Adhere to the following requirements for train makeup when handling DP Remote Locomotive Consists in the train:

<u>DP Remote Consist</u>	<u>Placement Requirements</u>
Single locomotive	Must have 5 loaded cars placed directly ahead of the DP Remote Locomotive Consist
Two or more locomotives	Must have 10 loaded cars placed directly ahead of the DP Remote Locomotive Consist
Manifest Trains with Auto Racks	Auto Racks must not be coupled directly ahead of, or behind the DP Remote Consist
Manifest Trains with Intermodal Spine Cars	Spine cars must be buffered with a minimum of 5 loaded cars ahead of and behind any DP Remote Consist
Solid Bulk Commodity Trains	No Placement Restrictions

A DP Remote Consist is a locomotive consist located at other than the head end of the train.

T. Hartwig
Superintendent Transportation

Yardmaster Notices in Effect:

Year of Issuance	Numbers
2016	001, 002
2019	001, 002, 003, 004